


**GS25/500/S/200/ES**


Essiccatore.


 Elettroventole di raffreddamento dal mod. **GS35**.

## SILENZIATI SU SERBATOIO MONOSTADIO E BISTADIO CON ESSICCATORE

ONE-STAGE AND TWO-STAGE SILENT COMPRESSORS ON TANK WITH DRYER  
 COMPRESSEURS SILENCIEUX SUR RÉSERVOIR MONO-STADE ET BI-STADE AVEC SECHEUR  
 EINSTUFIGE UND ZWEISTUFIGE SCHALLGEDÄMPFTE KOMPRESSOREN AUF TANK MIT TROCKNER

MODELLO Model	CODICE Code															
		Litri Liters	Litri/min Liters/min	CFM	min-1	Cilindri Cylinders	Stadi Stages	bar	psi	kW	HP	Volt	Hz	dB/A	L x P x H cm	Kg
GS25/500/S/200/ES	<b>AL 209</b>	24+200	500	17,6	1.450	2	1	10	145	3	4	400	50	67	150x51x147	125
GS28/500/S/300/ES	<b>AL 221</b>	300	500	17,6	1.450	2	2	10	159	3	4	400	50	67	162x51x147	130
GS35/600/S/300/ES	<b>AL 210</b>	300	600	21,2	1.450	2	2	10	159	4	5,5	400	50	65	162x62x155	218
GS38/650/S/300/ES	<b>AL 211</b>	300	650	23	900	2	2	10	159	4	5,5	400	50	68	162x62x155	239
GS38/850/S/300/ES	<b>AL 207</b>	300	850	30	1.150	2	2	10	159	5,5	7,5	400	50	68	162x62x155	246
GS50/1200/S/300/ES*	<b>AL 206</b>	300	1.182	42	1.100	2	2	10	159	7,5	10	400	50	68	162x62x155	291
GS35/600/S/500/ES	<b>AL 202</b>	500	600	21,2	1.450	2	2	11	159	4	5,5	400	50	65	200x62x165	287
GS38/650/S/500/ES	<b>AL 203</b>	500	650	23	900	2	2	11	159	4	5,5	400	50	68	200x62x165	308
GS38/850/S/500/ES	<b>AL 204</b>	500	850	30	1150	2	2	11	159	5,5	7,5	400	50	68	200x62x165	315
GS50/1200/S/500/ES*	<b>AL 205</b>	500	1.182	42	1100	2	2	11	159	7,5	10	400	50	68	200x62x165	360

\* CON AVVIAMENTO STELLA/TRIANGOLO - WITH STAR/DELTA STARTER - AVEC DEMARRAGE ETOILE/TRIANGLE - MIT STERN/DREIECK ANLASSEN

VOLTAGGI ED ESECUZIONI SPECIALI A RICHIESTA • VOLTAGES AND SPECIAL ASSEMBLIES ON REQUEST  
 TENSIONS ET FABRICATIONS SPÉCIALES SUR DEMANDE • SPANNUNGEN UND SONDERAUSFÜHRUNGEN AUF ANFRAGE