



CROSSAGE EVO PLUS



LAMBORGHINI
RECOMMENDED



5 YEAR WARRANTY
ON GEARBOX



SUPER-AUTOMATIC CENTER POST LEVER - NO LEVER TYRE CHANGER WITH BEAD BREAKER DISKS



Suitable for Tubeless tyre bead seating system (optional)

- Reinforced Chassis and Tower
- Tyre inflation by pedal (standard)



MOTOINVERTER

Faster, more accurate and reliable drive for your tyre changer.

- Equipped with **QX PLUS** mount/demount system [Giuliano Patent] with combined option through patented **Lever - No Lever** device.
- QuadraLock** system for total stiff locking of horizontal and operating arm.
- Operated by pedal and control console

BP1 PLUS pneumatic bead pressing arm [Giuliano Patent] lifts up automatically at the end of the mounting procedure, and moves back in rest position, with no need for the operator to change his working position (standard).

Vertical post with built-in air tank for tubeless tyre inflation and bead seating



SMART LOCK [Giuliano Patent] ultra-quick wheel clamping system, through cone and shaft with Smart Lock nut.



QX PLUS [Giuliano Patent]. By means of a control switch, the "NO LEVER" mode can be turned into a "LEVER" one.



Bead breaker disks are slightly but purposely misaligned with the rim center for a better and faster penetration and immediate bead loosening, **Center Driven Concept [Giuliano Patent]**

Tools Storage Box (standard)

Double rotation speed by pedal (motoinverter)

"Easy Access" extractable pedal box for quick service



220V-1ph
Inverter

Available in:
● Blue Trim
● Black Trim
● Red Trim

Double arm/disk air operated bead breaker system

Two disks for safe and fast bead breaking, perfect also for match-mounting and "seating" of the bead in its position.

A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



STANDARD FEATURES

Rim clamping range	12" - 34"
Max. tyre diameter	1200 mm (47")
Max. tyre width	406 mm (16") *
Bead breaker cylinder force at 10 Bar	11770 N (1200 kg)
Max. wheel weight	80 kg
Operating pressure	8-10 bar (116 - 145 Psi)
Power supply	220V - 1ph
Motor power	0,75 kW - 2 speed
Rotation speed	7 - 16 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	395 kg
Max. overall dimensions	1980x1880x2300 mm

* For reverse mounted wheels, variable according to rim features

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF
STANDARD ACCESSORIES

● Bead lifting lever ● Lube paste bucket and Brush ● Plastic tyre lever ● Plastic protectors for QX mounting/demounting tool ● 2 Plastic protectors for Smart Lock centering cone ● 2 Rubber protectors for clamping chuck and driving pin ● Reduction ring for clamping chuck ● Plastic bead pressing clamp ● Set of rubber protectors ● Adjustment knob for Smart Lock ● Plastic cone Ø 70 mm ● Spare O rings for Smart Lock ● Air lubricator, air filter/water trap ● Work gloves