

TYRE-CHANGERS - PAR-MOVE CONCEPT

PAR-MOVE SERIES - STRONGER THAN EVER!!

NEW

S119 PRO CP LNL



PAR-MOVE CONCEPT HIGH PERFORMANCE SUPER-AUTOMATIC CENTER POST LEVER - NO LEVER TYRE CHANGER WITH DUAL ASSIST ARM



Suitable for **Tubeless** tyre bead seating system (optional).



5 YEAR WARRANTY ON GEARBOX and PAR-MOVE



S119 PRO CP LNL

www.giuliano-automotive.com

Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [Giuliano Patent].

LNL SYSTEM [Giuliano Patent] can work either with or without bead lifting lever (standard).



MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.

Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version

Vertical tower with **built-in air tank**, provides tubeless tyre inflation and bead seating (optional), eliminating the need for a separate air tank.



HP119 Additional auxiliary helper system provides a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres.

Tyre inflation by pedal and Tools Storage Box (standard).

Manual **Press/Twist** clamping device.

Double rotation speed by pedal



Bead breaker **double effect** Cylinder \varnothing 200 mm.

"Easy Access" **extractable** pedal box for quick service.

Reinforced Chassis.
Fixed vertical tower and parallelogram operating arm [Patented] makes S119Pro CP LNL **extremely robust** and stiff, granting **increased rigidity** and eliminating all flexes.

Patented **PO SYSTEM** (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration.



Adjustable BB shovel stroke. Super-quick and Simple.



220V-1ph Inverter

Available in:
● Blue Trim
● Black Trim
● Red Trim

A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



STANDARD FEATURES

Rim clamping range	12" - 30"
Max. tyre diameter	1100 mm (43")
Max. tyre width	390 mm (15") *
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 Bar (145 Psi)
Power supply	220V - 1ph - Inverter (STND) 400V - 3ph, 2 speed, 110V - 1ph (OPT)
Motor power	0,75 kW (2 speed)
Rotation speed	7 - 16 rpm
Pre-set tyre inflating pressure	3,5 Bar (50 Psi)
Net weight	415 kg
Max. overall dimensions	1390 x 1310 x 2170 mm

* For reverse mounted wheels, variable according to rim features

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

● Bead lifting lever ● Lube paste bucket and Brush ● Plastic protectors for LNL mounting/demounting tool ● 2 Protectors for bead breaker shovel ● Lubricator + Pressure regulator ● Bucket support ● Press/Twist clamping device ● 2 Plastic protections for clamping device ● 2 Rubber protections for clamping chuck and driving pin ● Reduction ring for clamping chuck