

PAR-MOVE SERIES - STRONGER THAN EVER!!

NEW

S119 PRO DUO CP



PAR-MOVE CONCEPT HIGH PERFORMANCE SUPER-AUTOMATIC CENTER POST TYRE CHANGER WITH COMBINED TWO ASSIST ARMS



S119 PRO DUO CP

www.giuliano-automotive.com



5 YEAR WARRANTY ON GEARBOX and PAR-MOVE



Suitable for **Tubeless** tyre bead seating system (optional).



MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.

Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version

Robust fixed vertical tower with innovative **PAR-MOVE parallelogram operating arm** [Giuliano Patent].

Vertical tower with **built-in air tank**, provides tubeless tyre inflation and bead seating (optional), eliminating the need for a separate air tank.

BP1 PLUS pneumatic bead pressing arm [Giuliano Patent] lifts up automatically at the end of the mounting procedure, and moves back in rest position, with no need for the operator to change his working position (standard).



Reinforced Chassis. Fixed vertical tower and parallelogram operating arm [Patented] makes S119Pro DUO CP **extremely robust** and stiff, granting **increased rigidity** and eliminating all flexes.

Fitting head designed for both standard and low profiled tyre applications.

HP119 Additional auxiliary helper system (standard) provides a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres.

Manual **Press/Twist** clamping device.



Double rotation speed by pedal.

Tyre inflation by pedal and Tools Storage Box (standard).


Bead breaker **double effect Cylinder** ø 200 mm.

Patented **PO SYSTEM** (standard) automatically moves the bead breaker shovel back to the starting position, after its penetration.



"Easy Access" **extractable** pedal box for quick service.


Adjustable BB shovel stroke. Super-quick and Simple.



220V-1ph Inverter

Available in:
● Blue Trim
● Black Trim
● Red Trim

A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



STANDARD FEATURES

Rim clamping range	12" - 30"
Max. tyre diameter	1100 mm (43")
Max. tyre width	390 mm (15")*
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 Bar (145 Psi)
Power supply	220V - 1ph - Inverter (STND)
Motor power	400V - 3ph, 2 speed, 110V - 1ph (OPT)
Rotation speed	0,75 kW (2 speed)
Pre-set tyre inflating pressure	7 - 16 rpm
Net weight	3,5 Bar (50 Psi)
Max. overall dimensions	420 kg
	1750 x 1310 x 2170 mm

* For reverse mounted wheels, variable according to rim features

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

- Bead lifting lever ● Lube paste bucket and Brush ● Plastic protectors for mounting/demounting tool ● 2 Protectors for bead breaker shovel ● Lubricator + Pressure regulator ● Bucket support ● Press/Twist clamping device ● 2 Plastic protections for clamping device ● 2 Rubber protections for clamping chuck and driving pin ● Reduction ring for clamping chuck