

For low-mid volume shops, garages and repair shops.

## S225 EVO



### AUTOMATIC TILT BACK TYRE CHANGER WITH DUAL ASSIST ARM



5 YEAR WARRANTY  
ON GEARBOX




Discover on our website!



**Suitable for Tubeless tyre bead seating system (optional).**

Model with four control pedals, tilting tower, sliding horizontal arm and operating arm with manual lowering and locking by pushing button.



✓ Tilting tower, sliding horizontal arm with  $\varnothing$  41 mm operating arm.

✓ Vertical arm with return spring.

✓ Pneumatic locking of horizontal and operating arm.

✓ **HP LIGHT** dual assist arm to ease mounting operations of low profiled and UHP tyres (standard):

- Bead Pressing Roller
- Bead Pressing Pad



Plastic protectors

✓ Fitting head designed for both standard and low profiled tyre applications.

✓ Plastic protections on fitting head to **avoid any damage** to alloy rim.

✓ Tabletop thickness 12 mm.

✓ Two **powerful** clamping cylinders provide **uniform** clamping pressure.



art. 9242351

Additional roller tool arm for lower bead (optional).



art. 9242740

Additional bead lifting disk arm for lower bead (optional).



**Rubber coated jaw protectors.** Provides extra grip (optional).

✓ Bead breaker **double effect Cylinder**  $\varnothing$  200 mm.

✓ Tyre inflating gauge (optional).



✓ Tyre inflation by pedal (optional).

✓ Designed, built and engineered in Italy.



Available in:  
● Blue Trim  
● Black Trim  
● Red Trim



**PEDAL INFLATION SET.** Installed on the side of the tyre changer, provides inflation system on board the tyre changer, activated by pedal (optional).



### STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3 ph / 220V - 1 ph
Motor power	0,55 kW (3 ph)
Rotation speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	310 kg
Max. overall dimensions	1420x1740x2010 mm

\* By adjustable jaws

### STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

• Bead lifting lever • Jaw protectors for alloy rims • Plastic protectors for mounting/demounting tool (3 front + 3 rear) • Protectors for bead breaker shovel • Lubricator