

Solid and reliable design. Excellent quality-price ratio.

YouTube

Watch the video



5 YEAR WARRANTY ON GEARBOX



Discover on our website!

S226



AUTOMATIC TILT BACK TYRE CHANGER



Suitable for Tubeless tyre bead seating system (optional).



MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.

Available in 3ph-1 speed, 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version.

S226 PRO



HP4 (standard)

Technical specs (see S226)
Dimensions 1590x1820x1910 mm
Net weight 307 kg

✓ Reinforced Chassis and Tower.

✓ Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm.

✓ Fitting head designed for both standard and low profiled tyre applications.



Suitable for Patented **QX Leverless** mounting device for low profiled and UHP tyres (optional).

✓ Reliable and durable clamping system, with two cylinders. Tabletop thickness 12 mm.

✓ Designed, built and engineered in Italy.

✓ "Easy Access" extractable pedal box for quick service.

✓ Tyre inflation by pedal (optional).



PEDAL INFLATION SET.

Installed on the side of the tyre changer, provides inflation system on board the tyre changer, activated by pedal, (optional).



✓ Robust bead breaker arm.

✓ Bead breaker double effect Cylinder \varnothing 200 mm.



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



Available in:
● Blue Trim
● Black Trim
● Red Trim

STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1100 mm (43")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph/400V-3ph-2 speed 220V-1ph/220V-1ph-2 speed
Motor power	0,55 kW (3 ph)
Rotation speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	225 kg
Max. overall dimensions	1170x1820x1910 mm

* By adjustable jaws

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

● Bead lifting lever ● Lube paste bucket and Brush ● Plastic protectors for mounting/demounting tool ● 2 Protectors for bead breaker shovel ● Jaw protectors for alloy rims ● Lubricator + Pressure regulator ● Bucket support