

For motorcycle tyre specialists, servicing motorcycles, scooters and ATV tyres.

## S226 BIKE



**Sturdy, user friendly and problem solving** tyre changer to help best professionals in the field.



Discover on our website!

### AUTOMATIC TILT BACK TYRE CHANGER FOR MOTORCYCLES, SCOOTERS & ATV TYRES



**Kit of 4 motorcycles adaptors** with wider clamps, oversize / standard height (optional).

#### Automatic

Model with four control pedals, tilting tower, sliding horizontal arm and operating arm with manual lowering and locking by pushing button.



**5 YEAR WARRANTY ON GEARBOX**



Plastic protectors

✓ Reinforced Chassis.

✓ Fitting head designed for both standard and low profiled tyre applications.

✓ Tilting tower, sliding horizontal arm with  $\varnothing$  41 mm operating arm.



Suitable for **PRESS ARM ECO** additional pneumatic helper tower to ease mounting operations of low profiled and UHP tyres (optional):

✓ Plastic protections on fitting head to **avoid any damage** to alloy rim.

✓ Four motorcycle clamping jaws **adjustable** to 4 different positions: 6"-13", 10"-17", 14"-21", 17"-24".

✓ Tabletop thickness 12 mm, specially designed for motorcycle wheels.

✓ Two **powerful** clamping cylinders provide **uniform** clamping pressure.

✓ Tyre inflating gauge (optional). Tyre inflation by pedal (optional).

✓ "Easy Access" extractable pedal box for quick service



#### PRESS ARM ECO (optional)

Bead pressing pad

Bead lifting disk



✓ Bead breaker **double effect Cylinder**  $\varnothing$  200 mm.

✓ Designed, built and engineered in Italy.

✓ Robust and high-performance product for intensive use.

**BMW Motorrad approved version** is available through official BMW channels.



Available in:

- Blue Trim
- Black Trim
- Red Trim



**PEDAL INFLATION SET**. Installed on the side of the tyre changer, provides inflation system on board the tyre changer, activated by pedal (optional).



#### STANDARD FEATURES

Rim clamping from outside	6" - 24"
Max. tyre diameter	1110 mm (43")
Max. tyre width	240 mm (9,5")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V - 3 ph / 220V - 1 ph
Motor power	0,55 kW (3 ph)
Rotation speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	225 kg
Max. overall dimensions	1170x1820x1910 mm

#### STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

- Bead lifting lever ● Lube paste bucket and Brush ● Plastic protectors for mounting/demounting tool (3 front + 3 rear) ● 2 Protectors for bead breaker shovel ● Lubricator + Pressure regulator ● Bucket support