

Integrated Sonar, Led light, Laser Line. BE FASTER and more productive!

**NEW**  
**5825**



1100 mm 510 mm 75 Kg



S825

[www.giuliano-automotive.com](http://www.giuliano-automotive.com)

## DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH ADJUSTABLE LED DISPLAY, LASER LINE AND LED LIGHT



Advanced software for further upgrades\*.

✓ USB port for firmware updating via PC/notebook

✓ Intuitive, Easy-to-use Control Panel

✓ Complete with Wheel guard, cones and quick clamping ring nut

✓ Automatic measuring of wheel width by **SONAR (LA)**, standard.

### FUNCTIONS

- Automatic measuring of wheel diameter and distance
- Automatic START and STOP
- Static and dynamic balancing
- OPTIMATCH function
- Self-diagnosis and Self-calibration



**LED LIGHT**  
to illuminate working area.



**LASER LINE**  
for exact positioning of adhesive weights.




### SELF SELECTION MODE



Self-recognition of the Working program.

### SPECIAL ALU PROGRAM




Programs for selecting the best correction planes for any kind and shape of alloy rim.

✓ Pedal brake



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

### HIDDEN WEIGHT



• Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

### OPPOSITE POSITION



• Opposite Weight function (OPF), enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (at 6:00).

*\*The performance of the machine over time can improve, thanks to targeted updates.*

EXTENSIVE SELECTION OF STANDARD ACCESSORIES

### OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter and much more

*Find out more on our website!*

### STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	230V 1ph (50/60) Hz
Unbalance detection time	4,7 sec. (5 3/4"x14") 15 kg.
Balancing speed	< 150 rpm
Balancing precision	± 1 g
Net weight with guard	92 kg
Max. overall dimensions	1350x1150x1280±1540 mm

Available in: ● Blue Trim ● Black Trim ● Red Trim

### STANDARD ACCESSORIES



- Wheel guard
- Manual gauge for measuring wheel rim width
- Cones and quick clamping ring nut
- Counterweight pliers
- SONAR LA