

The best choice for the average tyre shop with budget goal.

SL22



Discover on our website!

AUTOMATIC TILT BACK TYRE CHANGER FOR CAR WHEELS 10" – 24"



Suitable for Tubeless tyre bead seating system (optional)

Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm

NEW



Suitable for **HP4 Dual Assist Arm** with 3 tools (optional):

Spring supported operating arm

CE inflating gauge (standard)

Fitting head designed for both standard and **low profiled** tyre applications

Tabletop thickness 12 mm

Reinforced Chassis

Bead Pressing Roller

Bead Lifting Roller

Bead Pressing Pad





Additional tilting roller tool for lower bead with an anti-collision joint.

Bead breaker **double effect Cylinder** \varnothing 200 mm., made in aluminum



Suitable for Tyre inflation by pedal (optional)




STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph / 220V-1ph
Motor power	0,55 kW (3 ph)
Rotation speed	7 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	220 kg
Max. overall dimensions	1240x1740x2010 mm

* By adjustable jaws

STANDARD ACCESSORIES



• Bead lifting lever • Plastic protectors for mounting/demounting tool • Lubricator + Pressure regulator • CE inflating gauge