

SILVERLINE



The best choice for the average tyre shop with budget goal.

YouTube
Watch the video



Discover New Brochures!

NEW

SL28 PRO DUO LNL



220V-1ph Inverter



SUPER-AUTOMATIC CENTER POST LEVER - NO LEVER TYRE CHANGER FOR CAR WHEELS 10" – 28"



MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.



Suitable for Tubeless tyre bead seating system (optional).

Robotic pipe to support operating arm.

Locking system for total stiff locking of horizontal and operating arm.

Ergonomic control console for a fast and intuitive work flow.

Bead pressing arm to ease mounting operations of low profiled and UHP tyres.

Twisting arm/disk air operated bead breaker system.


Lever-No-Lever tyre mounting / demounting system [Giuliano Patent], standard.

LNL SYSTEM [Giuliano Patent] can work either with or without bead lifting lever, standard.

Manual Press/Twist clamping device. Rim clamping up to 28".




"NO LEVER" MODE



Reinforced chassis and tower.



"LEVER" MODE



A very practical wheel lifter reduces effort and increases productivity (optional).

"Easy Access" extractable pedal box for quick service.

Tyre inflation by pedal (standard).

Control lever to manage movements of the tool.

Double rotation speed by pedal (220V - 1ph - Inverter).

"LEVER" & "NO LEVER" Mode control handle



STANDARD FEATURES

Rim clamping range	10" - 28"
Max. tyre diameter	47" (1200 mm)
Max. tyre width	406 mm (16") *
Bead breaker cylinder force at 10 Bar	12037 N
Max. wheel weight	80 kg
Operating pressure	8 - 10 bar (116 - 145 Psi)
Power supply	230V - 1Ph - 50/60 Hz with motoinverter
Motor power	0,75 kW - 2 speed
Rotation speed	7±16 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	350 Kg
Max. overall dimensions	1185 x 1960 x 2120 mm

* For reverse mounted wheels, variable according to rim features

STANDARD ACCESSORIES



EXTENSIVE SELECTION OF STANDARD ACCESSORIES

• Lube paste bucket 1 kg • Bead lifting lever • Plastic tyre lever • Plastic protections for LNL mounting/demounting tool • Plastic protections for centering cone • Rubber protections for clamping chuck • Bead pressing clamp (WDK clamp) • Filter + pressure regulator + lubricator • Press/Twist clamping device