

C-LINE

TITAN

XC 3600 EF - XC 3200 EF



Electrohydraulic underbody double scissors type lift, for tyre specialists, car workshops, and body repairers.



Description



Electrohydraulic underbody double scissors type lift, for tyre specialists, car workshops, and body repairers.

Alignment of the runways with a dual **MASTER/SLAVE** circuit (**two cylinders per runboard**) without mechanical safety racks.

Runboards version with flaps (**F**).

All models available in both on-floor and flush installation versions.

Adjustment bolts with rubber to cushion the end of the stroke



Runways with suspended flaps which also act as vehicle access ramps.



Generously sized, self-lubricating sliding blocks.



Special **lift linkage**, for lifting loads even from the lowest lift height.



Unique arm geometry for maximum stiffness and minimised space usage.

Technical data

| TITAN | XC 3600 EF | XC 3200 EF |
|--------------------------|-------------------------------|-------------------------------|
| Lift capacity | 3600 kg | 3200 kg |
| Lifting time | 45 s | 45 s |
| Motor | 400/230V-3kW-3ph-50 Hz | 400/230V-3kW-3ph-50 Hz |
| Lift max. lifting height | 2040 mm | 2040 mm |
| Lift minimum height | 105 mm | 110 mm |

Supplied accessories

- Self-lubricating bushings on all rotating parts
- Set of 4 rubber pads

Optional

- Pair of cross pieces and pads for off-road vehicles.
- Kit for pit installations.

Dimensions

TITAN XC 3600 EF / TITAN XC 3200 EF

